



AIS to Bluetooth
PPS-4-FF

\$ 399.00**



AIS to USB
PPS-3-USB

\$ 349.00**



AIS to Battery Bluetooth
PPS-4-BBT

\$ 489.00**

** Prices do not include taxes, shipping, or handling

GENERAL FEATURES:

- All adapters are complete and pre-configured prior to shipping
- Two switches that can correct for the most commonly seen Tx/Rx and pair errors standard
(Baud rate errors from the AIS can NOT be corrected by these devices. Users will need to refer to the AIS Manufacturer's User Manual for the correct setup)
- GREEN/RED** Bi-color LEDs for data transmission and polarity indication included
- 100-240 VAC power supplies with international fittings included with Bluetooth systems
(PPS-3-USB is powered by the USB Port and does not require external power)
- Bluetooth system cable is approx. 12". USB system includes 3' USB Cable & 6' Serial to Pilot Plug Cable
(Switchbox size and cable colors may vary slightly depending on availability at time of manufacture.)
- Custom cable lengths and pigtailed available upon request
- Installation instructions and Windows drivers (when applicable) included
- 6 Month Limited Warranty
- Patent Pending

Bluetooth Specs

BT v2.0/1.2/1.1 Compliant
Class 1 – transmit range up to 300' *
Uses standard BT Serial Port Profile and is compatible with all clients running under Windows™, PalmOS™, PocketPC™, Apple™, and other BT enabled platforms
Auto Discovery and Auto Connect modes
Weighs 8 oz. including power supply and adapters

*Transmit range may be less due to many factors, including environmental considerations. This device uses an internal antenna and has typical transmit ranges of 150-200'.

USB Adapter Specs

Adds 1 optically isolated RS422 to USB connection
Installs as a standard Windows™ COM port
ESD Surge Protection – 15KV
2000 VDC Optical Isolation
Powered by USB port. No external power required
COM port can support HyperTerminal™ or any other COM port number required
Supports Windows™ XP/2000/ME, LINUX™, and MAC™ OS9/X
Weighs 6 oz. excluding cables

Battery Bluetooth Specs

BT v2.0/1.2/1.1 Compliant
Class 1 – transmit range up to 300' *
Uses standard BT Serial Port Profile and is compatible with all clients running under Windows™, PalmOS™, PocketPC™, Apple™, and other BT enabled platforms
Auto Discovery and Auto Connect modes
Uses 2 AAA batteries – 1000mAh NiMH rechargeable batteries included
Auto-shutdown timer to save battery power
Weighs 10.4 oz. including batteries, battery charger /power supply and adapters
15+ hours continuous connection time on a single charge when using rechargeable batteries

How To Contact Us

E-mail or call for availability

E-mail: info@pilotplug.com Phone: 215-322-5441
<http://www.pilotplug.com>

Portable Pilot Solutions
c/o Observation Technologies, Inc.
136 Railroad Drive
Ivyland, PA 18974



AIS to Bluetooth

PPS-4-FF



AIS to USB

PPS-3-USB



AIS to Battery Bluetooth

PPS-4-BBT



Observation Technologies, Inc.